MERGER LRF THERMAL BINOCULARS

Features & Specs

Model	Merger LRF XL50	Merger LRF XP50	Merger LRF XQ35
Market release	2023	2022	2023
	SENSOR		
Sensor type	Microbolometer, uncooled, α-Si		
Sensor resolution, pixel	HD 1024x768	640x480	384x288
Pixel pitch, µm	12	17	17
Sensor NETD, mK	< 40	< 25	< 25
	DISPLAY		
Display type	AMOLED HD		
Display resolution, pixel	1024x768		
	OBJECTIVE LENS		
Lens	F50 / 1.0	F50 / 1.0	F35 / 1.0
Lens material		Germanium	
	FIELD PERFORMANCE		
Magnification, x	2.5 - 20	2.5 – 20	3 – 12
	(High image detail		
	across the whole		
	magnification range)		
Field of View, °	14 x 10.5	12.4 x 9.3	10.7 x 8
Detection range, m	2300	1800	1350
2 steamen range, m	VIDEO RECORDING		
Built-in videorecorder	Yes, .mp4 (with sound recording) / .jpeg		
Video / photo resolution, pixel	1024x768		
Built-in memory, Gb	64	16	16
,	POWER SUPPLY		
Battery type	Dual Li-Ion Power System: 3.2 A·h Changeable Battery (external) /		
May approximation times b	7	4.0 A⋅h Battery (internal	10
Max. operation time, h		8.5	
External power supply	USB Type-C (quick-charge supported) OPERATING AND PHYSICAL PARAMETERS		
Body material	Magnesium alloy		
Operating temperature, °C	-25 ÷ +50		
IP rating (IEC 60529)	IPX7 (waterproof)		
Dimensions, mm	197 x 140 x 72	196 x 143 x 76	181 x 133 x 68
Weight (with batteries), kg	0.95	0.95	TBD
Weight (with batteries), kg			
	8 (White Hot, Black Hot, Red Hot, Red Monochrome, Rainbow,		
Colour palettes	Ultramarine, Violet, Sepia)		
	Sensor sensitivity amplification adjustment (Normal, High, Ultra) / Smoothing filter / User mode		
Observation modes			
Wi-Fi	Yes, 2.5 / 5 GHz		
Supported mobile app	Stream Vision 2		
Language selection	English, German, Spanish, French, Russian, Italian, Portuguese, Dutch, Danish, Norwegian, Swedish, Polish, Czech, Hungarian		

And more:

- Classic binocular design
- Comfortable viewing experience with both eyes
- Precise laser rangefinder with 1000 m measuring distance
 - Proximity sensor for covert use